

Ceiling Mount Bracket for Optimal Coverage

Securely install a Lorex Pan-Tilt-Zoom security camera onto the ceiling with the ceiling mount bracket. This accessory is lightweight, yet, durable and aesthetically built.

Easy Installation

 Simply attach the security camera to the ceiling mount for optimal coverage.

Sturdy Construction

 Built of durable aluminum, with a loadbearing capacity of 15.4lbs./7kg.

Weather-resistant

 The cable connection is protected from extreme heat, cold, rain, and harsh wind.

Product Specifications

Material Aluminum and PC
Load Bearing 15.4 lb/ 7 kg
Pipe Thread G1 1/2"

Operating Temperature -40°F to 140°F / -40°C to 60°C

Operating Humidity <90% (RH)
Color White

Dimensions Φ 5.3 × 16.5" / Φ133.6 × 235.5 mm (pole) Φ 2.3 6" × 1.9" / Φ 60 × 49 mm (adapter)

Weight 1.7 lb / 0.78 kg (pole) 0.6 lb / 0.25 kg (adapter)

Package Information

 AUC-1W
 6-95529-04093-6

 Package
 Brown Box

 Package Weight
 2.3lb / 1kg

 Package Dimensions (W × D × H)
 5.4 × 5.4 × 9.9" / 137 × 137 × 252mm

 Package Cube
 0.17 cbf / 0.0047 cbm

Compatibility*

LNZ44P12B 2K HD Outdoor PTZ IP Camera
LZV2925B 1080p HD Outdoor PTZ Camera
E881AP 4K Ultra HD IP Pan-Tilt-Zoom Camera

What's in the box



Ceiling Mount Pole



Mount Adapter



Installation Kit



Tool Kit



Quick Start Guide

^{*} Compatible cameras and junction boxes sold separately. For a full compatibility list please visit www.lorex.com/pages/compatibility