# LOREX

## 4K Smart Security Lighting IP Wired Dome Camera

#### PRODUCT SPECIFICATIONS

#### General

Video Transmission Technology Image Sensor Video Format Video Compression

#### Optical

Viewing Angle (Diagonal) Lens/Lens type

#### Video Output

Resolution/Frame rate

Effective Pixels

HDR

Termination

#### Audio

Microphone/Speaker

Siren

#### Two-way Talk

#### **Night Vision**

Ambient Nighttime Conditions

Total Darkness

**Color Night Vision** 

Smart Motion Detection Plus

Face Detection

Mask Detection

Package Detection

Supports in App Quick Messaging

Active Deterrence

IP	
8MP/4K 1/2.8" CMOS	
NTSC	

H.265/H.264 (Main Stream & Sub Stream)

127° 2.8mm F1.6/ Fixed

4K(8MP)@15fps, 5MP@30fps, 1080p@30fps, 720p@30fps H:3840 x V:2160 Yes

RJ45

Yes/Yes Yes (Siren sound options available)

#### Yes

150ft (45m)

98ft (30m)

Yes

Yes <sup>4</sup> - Person and Vehicle Detection

Yes<sup>4</sup>

Yes<sup>8</sup>

Yes - package missing or package left behind <sup>1</sup>

k Yes

Yes - Warning Light + Siren + Pre Recorded Message + Smart Security Lighting <sup>1</sup>

#### Additional Specifications

Camera Housing Material		Aluminum Alloy		
SD Card Slot		Yes*		
Power Requirements		PoE (Power over Ethernet Class -802.3af)/12V DC		
Power Consumption (max)		660mA / 9.5W		
Camera Dimensions (W x D x H)		4.8" x 4.8" x 4.4" (122 x 122 x112mm)		
Camera Weight		1.1lbs / 0.5kg		
Operating Temperature		-22°F ~ 140°F /-30°C ~ 60°C		
Humidity		< 95% RH		
Environmental Rating		IP67 (Indoor/Outdoor)		
MODEL INFORMATION				
E896DD - White	Brown Box		6-95529-05029-4	
E896DD-E - White	Retail Sleeve Box		6-95529-05062-1	
E896DDB - Black	Brown Box		6-95529-05028-7	
Package Weight	3.55lb / 1.6kg			
Package Dimensions (W × D × H)	11.4 × 6.3 × 5.1" / 290 × 160 × 130mm			
Package Cube	0.25cbf / 0.007cbm			

Disclaimers:

1. Compatible with select Lorex Network Video Recorders HD recorders. For a full list of compatible recorders visit: www.lorex.com/compatibility 2. Color nighttime video typically switches to black & white IR night vision when there is not sufficient ambient light to ensure optimal low-light image quality. 3. Stated IR illumination range is based on ideal conditions in typical outdoor nighttime ambient lighting (up to 98ft/30m in total darkness). Actual range and image clarity depends on installation location, viewing area and light reflection/absorption. 4. For Face Detection to operate, this camera requires a connection to a compatible Lorex Network Video Recorder with smart face detection technology. For a list of compatible recorders please visit: www.lorex.com/compatibility 5. Audio recording is disabled by default. Audio recording without consent is illegal in certain jurisdictions. Lorex Technology does not assume liability for any use of its product that fails to conform with local laws. 6. Not intended for submersion in water. Installation in a sheltered location recommended. 7. Cable length is dependent on product configuration. See product packaging for details 8. Mask Detection is compatible with select Lorex Network Video Recorders. For a full list of compatible recorders visit: www.lorex.com/compatibility \*A microSD card can be inserted for independent recording. Data can be accessed through the camera using a web browser but will not upload to the NVR or to the cloud for mobile app viewing. Lorex products are designed for consumer and business use only and not for US federal governments, federally-funded projects or contractors subject to NDAA. Lorex Corporation

10440 Little Patuxent Parkway, Ste, 300, Columbia, MD 21044, United States

### E896DD Series lorex.com

As our product is subject to continuous improvement, Lorex Technology & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incur gary obligation. E&OE. (23-0012-LOR) 03272024-4